

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 :

B01D 53/46

A1

(11) International Publication Number:

WO 96/16720

(43) International Publication Date:

6 June 1996 (06.06.96)

(21) International Application Number:

PCT/JP95/02415

(22) International Filing Date:

28 November 1995 (28.11.95)

(30) Priority Data:
6/294651

29 November 1994 (29.11.94)

JP

(71) Applicant (for all designated States except US): TEISAN
KABUSHIKI KAISHA (JP/JP); Nihon Gas Kyokai Building
7F, 15-12, Toranomon 1-chome, Minato-ku, Tokyo 105
(JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): IBARAKI, Yoshihiro
(JP/JP); Teisan Kabushiki Kaisha, 9-1, Shinonome 1-chome,
Koto-ku, Tokyo 135 (JP). INA, Hidekazu (JP/JP); Teisan
Kabushiki Kaisha, 9-1, Shinonome 1-chome, Koto-ku,
Tokyo 135 (JP). KAWANAKA, Hideji (JP/JP); Teisan
Kabushiki Kaisha, 9-1, Shinonome 1-chome, Koto-ku,
Tokyo 135 (JP).

(74) Agents: SUZUYE, Takchiko et al.; Suzuye & Suzuye, 7-2,
Kasumigaseki 3-chome, Chiyoda-ku, Tokyo 100 (JP).


(81) Designated States: US, European patent (AT, BE, CH, DE,
DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published

With international search report.

Before the expiration of the time limit for amending the
claims and to be republished in the event of the receipt of
amendments.

(54) Title: EXHAUST GAS TREATMENT UNIT AND METHOD



(57) Abstract

The present invention relates to an exhaust gas treatment unit which possesses a stable treating capacity, with a reduced running cost. The exhaust gas treatment unit removes noxious gases such as monosilane contained in an exhaust gas by thermal decomposition. The exhaust gas treatment unit includes a heating drum (5) into which the exhaust gas and oxygen or air are introduced and a heating source (6) disposed on the outer periphery of the heating drum (5) so as to heat the inside of said heating drum (5). A temperature sensor (14) detects the temperature of the inside of said heating drum (5) in the vicinity of its outlet and a controller (16) controls the heating source (6) in accordance with a detected temperature value from the temperature sensor (14) so that the temperature of the inside of said heating drum (5) in the vicinity of the outlet is maintained within a predetermined temperature range.

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

- 1 -

DESCRIPTION

EXHAUST GAS TREATMENT UNIT AND METHOD

1. Field of the Invention

5 The present invention relates to an exhaust gas treatment unit for subjecting an exhaust gas discharged from a semiconductor manufacturing installation or the like to a treatment for removing harmful substances, and more particularly, to an exhaust gas treatment unit for removing harmful gases such as monosilane (SiH_4), phosphine (PH_3),
10 hydrogen nitride (NH_3) and nitrogen fluoride (NF_3) contained in an exhaust gas by thermally oxidative decomposition.

2. Description of the Related Art

15 In the manufacture of semiconductors, an exhaust gas is generated which contains noxious gases such as SiH_4 , PH_3 , NH_3 and NF_3 . In accordance with the law (High Pressure Gas Control Law), manufacturers are obligated to install an exhaust gas treatment unit in order to treat the discharged exhaust gas and to discharge the exhaust gas only after the noxious gases have been removed or made harmless. The law
20 sets Threshold Limit Values (TLV) for noxious gases which are the maximum allowable amounts of these gases which may be present in discharged exhaust gases. Known types of exhaust gas treatment units for removal of these gases include a chemical reaction type treatment unit for removing
25 noxious gases by an oxidative or neutralization reaction using a neutralizing agent such as metal oxides or caustic soda (sodium hydroxide). Other known types of exhaust gas treatment units include wet scrubber type units or combustion type units which burn the exhaust gas using a gas
30 burner.

BEST AVAILABLE COPY

- 2 -

In conventional exhaust gas treatment units, such as those mentioned above, there are various problems. In a chemical reaction type treatment unit high expense and substantial labor are required for exchanging the chemical agents or metal oxides used in the treatment. In the case of a wet scrubber type treatment unit, large amounts of washing water and an absorbing liquid are required. In addition, a waste water treatment installation is necessary to treat the washing water.

In the case of a combustion type treatment unit, a combustion improver such as hydrogen or methane and a large amount of air or oxygen are necessary for combustion. A water cooling installation is also necessary for cooling the exhaust gas because the exhaust gas exit temperature in a combustion type treatment unit is high. Furthermore, there is a problem with combustion treatment in that deposits such as reaction products are easily deposited on the inside of a combustion reactor which must be periodically removed.

OBJECTS AND SUMMARY

It is therefore an object of the present invention to produce an exhaust gas treatment unit in which the aforementioned problems are addressed.

In order to achieve the aforementioned object according to the present invention, an exhaust gas treatment unit for removing noxious gases contained in an exhaust gas by thermal decomposition includes a heating drum into which the exhaust gas and oxygen are introduced, a heating source disposed on the outer periphery of the heating drum so as to heat the inside of the heating drum, a temperature detection means for detecting the temperature of the inside of the heating drum in the vicinity of its outlet, a control means for controlling the heating source in accordance with a detected value from the temperature detection means so that

- 3 -

the temperature of the inside of the heating drum in the vicinity of its outlet is maintained within a predetermined temperature range, and an air-cooled type cooling device connected to the outlet of the heating drum. In addition, the predetermined temperature range within the heating drum is preferably 350°C - 500°C.

BRIEF DESCRIPTION OF THE DRAWING FIGURES

The invention will be described in greater detail with reference to the accompanying drawings, wherein:

Fig. 1 is a schematic view of one embodiment of the exhaust gas treatment unit according to the present invention; and

Fig. 2 is a graph of experimental results obtained by using the exhaust gas treatment unit according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1 is a schematic view illustrating one embodiment of the exhaust gas treatment unit according to the present invention. The exhaust gas treatment unit of Fig. 1 is provided for treating and removing SiH_4 contained in an exhaust gas consisting mainly of nitrogen gas N_2 coming from a semiconductor manufacturing installation (not shown).

The exhaust gas treatment unit includes a heating device 1, a cooling device 2, and a filtering device 3. The heating device 1 heats the exhaust gas and air or oxygen introduced to the heating device. The heated SiH_4 in the exhaust gas is oxidatively decomposed and is converted to harmless silicon oxide (SiO_2). The cooling device 2 cools the treated gas discharged from the heating device 1 and the filtering device 3 removes the harmless SiO_2 from the treated gas. In order to prevent the exhaust gas or the

- 4 -

treated gas from being released to the atmosphere, the heating device 1, cooling device 2, and filtering device 3 are preferably accommodated in a casing 4 which is ventilated.

5 In the heating device 1 of the present invention, when the inside of the heating device is heated by a heating source, noxious gases such as SiH_4 , in the exhaust gas are thermally decomposed by the heat. In order for the noxious
10 gases to be decomposed, the quantity of air or oxygen introduced into the heating drum must be of a sufficiently minimum quantity to allow the oxidation of the oxidatively decomposable noxious gases.

By controlling the heating source with a temperature detection means and a control means, the temperature of the
15 inside of the heating device 1, and especially in the vicinity an outlet of the heating device is kept almost constant and hence the oxidative decomposition reaction is stabilized. After the thermal oxidative decomposition, the treated gas which is discharged from the outlet of the
20 heating drum is cooled down to a desired temperature by means of the air-cooled type cooling device 2.

The heating device 1 is composed of a cylindrical heating drum 5 and a cylindrical electric heater 6 disposed so as to surround the periphery of the heating drum 5. The
25 heating drum 5 is positioned within the casing 4 with an axis of the heating drum substantially vertical. An inlet nozzle 7 at the upper end of the heating drum 5 is connected to an exhaust gas introduction pipe 8 for introducing an exhaust gas from a semiconductor manufacturing installation.
30 An air introduction pipe 9 for introducing air containing oxygen which is necessary for oxidizing the SiH_4 in the exhaust gas is connected to the exhaust gas introduction pipe 8. The air introduction pipe 9 has a flow rate regulation valve 10 provided therein. By adjusting this
35 flow rate regulation valve 10, air in an amount

- 5 -

corresponding to the amount of oxygen used in oxidation of the SiH_4 in the exhaust gas can be supplied into the heating drum 5.

5 In the embodiment illustrated in Fig. 1, a gas header 11 is provided for removing oxidation products from the interior surfaces of the heating drum 5. The gas header 11 is filled with nitrogen or air under pressure and is connected to the exhaust gas introduction pipe 8 by way of a header gas introduction pipe 12. The header gas
10 introduction pipe 12 is provided with a valve 30 in order to instantaneously send out compressed nitrogen or the like into the heating drum 5 so that oxidation products deposited on the inner wall surfaces of the heating drum 5 are shaken down off the wall surfaces of the drum.

15 Temperature sensors 13,14 are disposed at the upper portion and the lower portion of the inside of the heating drum 5. A temperature sensor 15 is also attached at the inner surface of the electric heater 6 between the electric heater and the heating drum 5. The temperature sensors
20 13,14,15 are connected to a controller 16 for controlling the various valves and the electric heater 6. The controller 16 is adapted to receive detected temperature signals from the temperature sensors 13,14,15 and to control the electric heater 6 and the air flow rate regulation valve
25 10 so that the thermally oxidative decomposition of SiH_4 is properly carried out within the heating drum 5.

An outlet nozzle 17 at the lower end of the heating drum 5 is connected to the cooling device 2. The cooling device 2 is of an air cooled type, and includes an air-cooled pipe equipped with fins (hereinafter referred to as
30 "an air-cooled finned pipe") 18 connected to the outlet nozzle 17 of the heating drum 5 and a fan 19 for forcibly passing air over the fins of the air-cooled finned pipe 18. In the embodiment of Fig. 1, a temperature sensor 20 is
35 provided inside of the outlet portion of the air-cooled

- 6 -

finned pipe 18. In accordance with a detected temperature signal from this temperature sensor 20, the controller may determine whether the air-cooled finned pipe 18 and the fan 19 are operating properly to sufficiently cool the exhaust gas.

The outlet end of the air-cooled finned pipe 18 is connected to the filtering device 3. The filtering device 3 serves to remove fine particles of SiO_2 , resulting from oxidation of the SiH_4 and other oxidation products contained in the treated gas by filtration. Preferably, a bag filter is used to remove the oxidation products such as the fine particles of SiO_2 . Other dust removing equipment, for example a cyclone, can also be used.

The rear stage of the filtering device 3 in the embodiment of Fig. 1, is preferably connected to a harmful substance removing device 21 for a final treatment of the exhaust gas. The exhaust gas exiting from the harmful substance removal device is exhausted by an exhausting blower 22. Although the removing device 21 and the blower 22 may be accommodated in the casing 4, they are optional devices and could also be accommodated as a separate unit in a second casing 23, as illustrated in the drawing.

The harmful substance removing device 21 is preferably a so called dry chemical treatment device which is adapted to completely remove the extremely small quantity of harmful gases remaining in the treated gas by a treatment using proper chemicals agents. A pipe 24 between the filtering device 3 and the harmful substance removing device 21 is connected a by a by-pass pipe 25 to the exhaust gas introduction pipe 8. By controlling a valve 26 in the exhaust gas introduction pipe 8 and a valve 27 in the by-pass pipe 25, accordingly, it becomes possible to directly introduce the exhaust gas into the harmful substance removing device 21. This by-pass pipe 25 serves also to back up the heating device 1 when any problems occur

- 7 -

therein.

The outlet of the harmful substance removing device 21 is connected the exhausting blower 22. The terminal end of an exhaust pipe 28 extending from the discharge port of the exhausting blower 22 opens outside of the casing 23. Because of the existence of this exhausting blower 22, the whole interior of the exhaust gas treating system illustrated in the drawing is at a negative pressure. Therefore, it is possible to introduce air for oxidation into the heating drum 5 by suction directly from the atmosphere. It is not necessary to provide a compressed air cylinder or the like to introduce the oxidation air to the heating drum.

In such a construction as mentioned above, the exhausting blower 22 is constantly driven when the exhaust gas treatment unit is in a normal running condition. The exhaust gas and air are consequently sucked into the heating drum 5 through the exhaust gas introduction pipe 8 and air introduction pipe 9, respectively. Since SiH_4 in the exhaust gas is oxidized when it is brought into contact with air, it can be determined from the temperature detected by the temperature sensor 13 provided in the upper portion of the heating drum 5, that the exhaust gas and air have been introduced. In a case where the temperature detected by the temperature sensor 13 exceeds a predetermined value, it can be determined that the concentration of SiH_4 in the exhaust gas has been increased over a normal quantity. In order to avoid any danger, a danger signal will be produced when the temperature exceeds the predetermined value. The quantity of air to be introduced into the heating drum 5 will then be adjusted to increase the air flow according to the danger signal. In addition, an amount of oxygen necessary for carrying out the thermally oxidative decomposition of SiH_4 contained in the exhaust gas is sufficiently supplied by the air supply, as opposed to a combustion type exhaust gas

- 8 -

treatment unit using a gas burner or the like were larger amounts of oxygen are required.

5 Since the inside of the heating drum 5 is heated by the electric heater 6, the oxidative reaction of SiH_4 in the exhaust gas introduced into the heating drum 5 and oxygen in the air is accelerated. In a case where the temperature detected by the temperature sensor 14 provided in the lower portion of the heating drum 5, i.e. in the vicinity of the outlet portion thereof, is 350°C or more, the concentration of SiH_4 remaining in the treated gas discharged from the heating drum 5 is 1 ppm or less because almost 100% of the SiH_4 in the exhaust gas has decomposed. This is an excellent value that is remarkably lower than the TLV value of 5 ppm specified by law.

15 Experimental results obtained when an exhaust gas is actually subjected to a thermally oxidative decomposition by use of the exhaust gas treatment unit equipped with the heating drum 5 are shown in Fig. 2. In this experiment, two kinds of exhaust gases were used in which the concentrations of SiH_4 were 0.58% and 0.61%. In the case of the exhaust gas in which the concentration of SiH_4 was 0.58%, the experiments were carried out at exhaust gas flow rates regulated to be 215 ~ 225 l/min and 85 ~ 110 l/min. In the case of the exhaust gas in which the concentration of SiH_4 was 0.61%, the experiment was carried out at an exhaust gas flow rate of 215 ~ 225 l/min. As can be seen from Fig. 2, it is exhibited that when the temperature of the outlet portion of the heating drum 5 is 250°C , the rate of decomposition of SiH_4 is as high as 80% in each case, and when the temperature is 350°C or more, the rate of decomposition thereof is nearly 100%. In other words, if the temperature of the outlet portion inside of the heating drum 5 is maintained at 350°C , SiH_4 in the exhaust can be almost completely decomposed so as to be made harmless
35 irrespective of variations in the flow rate of the exhaust

- 9 -

gas and the concentration of SiH_4 . When the outlet temperature becomes $1,000^\circ\text{C}$ or more, on the other hand, nitrogen in the exhaust gas and in the air is oxidized to produce NO_x .

5 In order to enhance the cooling efficiency in the cooling device 2, it is preferred that the temperature of the gas discharged from the heating drum 5 is made as low as possible. Accordingly, the controller 16 is adapted to receive a detected temperature signal from the temperature
10 sensor 14 and to control the electric heater 6 so that the temperature of the outlet portion inside of the heating drum 5 is maintained within a range of 350°C - 500°C . After the electric heater 6 has been adjusted, another detection signal is fed back from the temperature sensor 15, and hence
15 the temperature regulation is rapidly carried out.

The exhaust gas which has been heated so as to be oxidatively decomposed is discharged from the outlet nozzle
17 of the heating drum 5, and is then introduced into the air-cooled finned pipe 18 of the cooling device 2. While
20 flowing through this air-cooled finned pipe 18, the treated gas is cooled down by air from the fan 19 passing over the fins. In a case where the temperature of the treated gas which has reached the outlet portion of the air-cooled
finned pipe 18 is higher than a predetermined temperature,
25 the fan 19 is determined to be abnormal and a warning signal will be produced. In addition, the high temperature air which has received heat from the air-cooled finned pipe 18 is discharged from a ventilation duct 29 provided on the upper portion of the casing 4 to the atmosphere.

30 The treated gas which has been cooled down in the cooling device 2 is then introduced into the filtering device 3 so as to be freed of fine particles of the harmless SiO_2 and the like produced by the thermally oxidative decomposition of the SiH_4 . Since the concentration of SiH_4 ,
35 in the treated gas which has been passed through the

- 10 -

filtering device 3 is 1 ppm or less, it is permissive to discharge this treated gas directly to the outside atmosphere. In order to ensure the perfect treatment of the exhaust gas in the illustrated embodiment the harmful substance removing device 21 is connected to the rear stage of the filtering device 3. An extremely fine amount of SiH_4 remaining in the treated gas is, therefore, completely removed by its oxidative reaction in the harmful substances removing device 21. Thus, the gas which has been finished in the exhaust gas treatment as mentioned above is released from the exhausting blower 22 to the atmosphere outside of the casing 23 through the exhaust pipe 28.

The foregoing description relates to a usual treating situation. In a case where any abnormality is detected in the heating device 1 for any reason, the valve 26 is closed and the valve 27 is opened in accordance with an instruction from the controller 16. In such a case, the exhaust gas is introduced directly into the harmful substance removing device 21 so that SiH_4 in the exhaust gas is chemically removed and the heating device is by-passed. Furthermore, in a case where any gas not suitable for being subjected to the thermally oxidative decomposition is admixed in an exhaust gas, it is also possible that the valves 26, 27 can be controlled to send the exhaust gas directly into the harmful substance removing device 21.

The heating drum 5 is preferably shaped in a simple cylindrical form and has no unevenness on its inner wall surface so that it is more difficult for oxidation products to be deposited on the inner wall surface of the heating drum 5. In a case where the treatment of an exhaust gas is continued for a long period of time, however, oxidation products may be deposited on the inner wall surface of the heating drum 5. In such a case, the valve 30 is opened to instantaneously supply a large amount of compressed nitrogen or compressed air from the gas header 11 into the heating

- 11 -

drum 5, whereby such deposits on the inner wall surface of the heating drum 5 can be instantaneously removed.

Although the exhaust gas treatment unit according to the aforementioned embodiment is adapted to remove SiH_4 from an exhaust gas stream, the invention is also applicable to various noxious gases such as PH_3 , NH_3 , NF_3 , TEOS, TMB and C_2F_6 . In a case where another gas is treated, it will be easily understood that it is necessary to control the temperature of the outlet portion of the heating drum 5 according to the particular gas.

Even in the case of a gas which cannot be completely decomposed, in the heating drum 5, the complete treatment of such a gas can be carried out by the exhaust gas treatment unit in combination with a chemical treatment unit as shown in the embodiment of Fig. 1.

As can be seen from the foregoing description, the present invention exhibits many advantages. Since the exhaust gas treatment unit according to the present invention is constructed such that the inside of the heating drum is heated by a heating source such as an electric heater provided in the outside and noxious gases in an exhaust gas are heated by its heat so as to be oxidatively decomposed, chemical agents and metal oxides as used in a chemical reaction type exhaust gas treatment units are unnecessary, and washing liquid and absorption liquid as used in a wet scrubber are also unnecessary.

In addition, in the exhaust gas treatment unit according to the present invention, fuel for combustion and cooling water are unnecessary as opposed to a combustion type exhaust gas treatment unit using a gas burner or the like. Accordingly, the running cost of the exhaust gas treatment unit according to the present invention is remarkably decreased, as compared with the conventional treatment units.

Since the structure of the heating drum is simple, the

- 12 -

attachment and separation and the maintenance of the heating drum are also simplified. In addition, it is difficult for oxidation products to be deposited on the inside of the heating drum by virtue of its structure, and hence the heating drum can be operated continuously for long periods of time. Since the heating source in the present invention is not in direct contact with the exhaust gas less heat from the heating source is consumed. In addition, due to the controlled temperature of the exhaust gas at the outlet portion of the heating drum the decomposition reaction is stable.

In the exhaust gas treatment unit according to the present invention, the quantity of air for oxidation is controlled to a minimum quantity necessary for decomposing the noxious gases. In contrast, a large amount of air is required combustion type units where a gas burner is used. As a result, the power required for introduction of air is also reduced. Finally, since the treated gas is cooled down by the air-cooled type cooling device, there is no need for water as a cooling medium. Accordingly, there is no need for supplying water or the like and for providing any treating apparatus for the water, thus, the cooling device can be made simple in structure.

While the invention has been described in detail with reference to a preferred embodiment thereof, it will be apparent to one skilled in the art that various changes and modifications can be made, and equivalents employed, without departing from the spirit and scope of the invention.

- 13 -

C L A I M S

1. An exhaust gas treatment unit for removing noxious gases contained in an exhaust gas by thermal decomposition comprising:

a heating chamber into which exhaust gas and oxygen are introduced, the heating chamber having an outlet;

a heating source disposed at an outer periphery of said heating chamber so as to heat an inside of said heating chamber;

a temperature detector for detecting a temperature of the inside of said heating chamber in a vicinity of the outlet and outputting a detected temperature value;

a controller for controlling said heating source in accordance with the detected temperature value from said temperature detector so that the temperature of the inside of said heating chamber in the vicinity of the outlet is maintained within a predetermined temperature range; and

a cooling device connected to the outlet of said heating chamber.

2. An exhaust gas treatment unit according to claim 1, wherein the predetermined temperature range is 350° ~ 500°C.

3. An exhaust gas treatment unit according to claim 1, wherein a flow of exhaust gas and a flow of oxygen into the heating chamber are each controlled by a valve and wherein the exhaust gas and oxygen are introduced into the heating chamber through a nozzle.

4. An exhaust gas treatment unit according to claim 1, further comprising a filtering device for removing oxidation products from a cooled exhaust gas exiting the cooling device.

- 14 -

5. An exhaust gas treatment unit according to claim 1, wherein the cooling device is an air-cooled type cooling device.

6. An exhaust gas treatment unit according to claim 5, wherein the air-cooled type cooling device includes a cooling pipe having fins on an exterior surface thereof and a fan for forcing cooling air across the fins.

7. An exhaust gas treatment unit according to claim 1, further comprising means for removing oxidation products from an inside surface of the heating chamber.

8. An exhaust gas treatment unit according to claim 7, wherein the means for removing oxidation products includes a compressed gas source for introducing compressed gas into the heating chamber to remove oxidation products which have been deposited on the inside surface of the heating chamber.

9. An exhaust gas treatment unit according to claim 1, wherein the heating chamber is a substantially cylindrical heating drum.

10. An exhaust gas treatment unit according to claim 9, wherein the heating source is a cylindrical electric heater disposed around the outer periphery of the heating drum.

11. An exhaust gas treatment unit according to claim 9, wherein the substantially cylindrical heating drum has an axis which is positioned vertically.

- 15 -

12. An exhaust gas treatment unit according to claim 1, wherein the heating chamber and the cooling device are positioned within a ventilated casing to prevent exhaust gas from being released to the atmosphere.

13. A method of exhaust gas treatment for removing noxious gasses contained in an exhaust gas comprising:
introducing an exhaust gas containing noxious gasses into a heating chamber;
introducing oxygen into the heating chamber;
heating the exhaust gas so as to thermally oxidatively decompose the noxious gasses;
controlling the temperature of the heating chamber by controlling a heating source in accordance with a temperature value detected by a temperature sensor within the heating chamber; and
cooling the exhaust gas exiting the heating chamber.

14. A method of exhaust gas treatment according to claim 13, further comprising a step of filtering the cooled exhaust gas to remove oxidation products.

15. A method of exhaust gas treatment according to claim 13, wherein the heating step causes SiH_4 in the exhaust gas to be oxidatively decomposed and converted to SiO_2 .

16. A method of exhaust gas treatment according to claim 15, further comprising a step of filtering the exhaust gas to remove the SiO_2 .

17. A method of exhaust gas treatment according to claim 13, wherein the temperature of the heating chamber is controlled to between $350^\circ - 500^\circ\text{C}$.

- 16 -

18. A method of exhaust gas treatment according to claim 13, further comprising a step of removing oxidation products from an inside surface of the heating chamber by introducing pressurized gas to the heating chamber.

19. A method of exhaust gas treatment according to claim 13, wherein the step of cooling the exhaust gas includes cooling the exhaust gas in an air-cooled device.

1/2




Fig. 1

2/2




Fig. 2

INTERNATIONAL SEARCH REPORT

International application No.
PCT/JP 95/02415

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: B01D 53/46

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: B01D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP, A1, 0611140 (THE BOC GROUP PLC), 17 August 1994 (17.08.94), column 2; column 4 - column 5, claims 1-5, 11, abstract	1-4, 9-11, 13-14, 17
A	---	5-8, 12, 15-16, 18-19
X	EP, A1, 0597393 (JAPAN PIONICS CO., LTD.), 18 May 1994 (18.05.94), page 3, line 28 - page 4, line 36, claims 1, 11, abstract	1-4, 13-14

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

& document member of the same patent family

Date of the actual completion of the international search

9 February 1996

Date of mailing of the international search report

01-04-1996

Name and mailing address of the ISA/
European Patent Office, P.B. 5818 Patentlaan 2
NL-2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Britt-Marie Lundell

INTERNATIONAL SEARCH REPORT

Information on patent family members

05/01/96

International application No.

PCT/JP 95/02415

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A1- 0611140	17/08/94	NONE	
EP-A1- 0597393	18/05/94	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☒ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.